

# Technical information

## Atmoz 2-90



### Characteristics

- With two sealing bars as standard (front/rear)
- Double seal as standard (two sealing wires)  
Optional at no extra cost: Cut-off seal/Wide seal (10 mm)
- Easy-to-remove silicone holders for easy cleaning
- Digital time control with ten-program memory as standard
- Flat working plate
- Supplied with one layer of insert plates for a faster cycle and good product positioning
- Stainless steel casing

### Options

- 1-2 Cut-off seal
- Sensor control
- Liquid control
- Advanced Control System (ACS)
- Gas flush (incl. compressed air connection)
- Soft Air to protect the product and vacuum bag
- 160 m<sup>3</sup>/h vacuum pump
- (Lightweight) bag clamp

### Accessories

- Thermal label printer (only in combination with ACS)
- Inclined insert plate (for liquids and powders)
- Second layer of insert plates
- Maintenance set for standard maintenance



Specs	Atmoz 2-90
Chamber LxWxH (mm)	870x880x280
Machine LxWxH (mm)	1320x1965x1105
Voltage	400V-3-50Hz 230V-3-50Hz 220V-3-60Hz 200V-3-50/60Hz
Pump capacity 50 Hz/60 Hz (m <sup>3</sup> )	300 / 360
Machine cycle 50 Hz/60 Hz (sec.)	15 - 40 / 13 - 35
Power (kW)	5,5 - 6,6
Weight (kg)	770
Net seal length (mm)	2 x 880
Standard sealing bar configuration	

### Dimensions mm

